



UD2-LX MultiMedia



PROFILE

The IGEL multiprotocol thin client, based on a system-on-chip (SoC) design, is the economical, space- and energy-saving entry-level device with high-performance multimedia acceleration for Citrix ICA/HDX and Microsoft's RemoteFX. With four USB ports, the UD2 models allow connection of all commonly used peripheral devices.

FEATURES AND BENEFITS

- ▶ **Multiprotocol system-on-chip (SoC) device**
VMware View with RDP and PCoIP, optimized for Citrix ICA/HDX, certified for Microsoft RemoteFX and multimedia playback.
- ▶ **Slim Design**
The perfect companion for any workplace due to the small form factor and the latest design.
- ▶ **VESA mountable** (optional)
Mountable on the back of a monitor with the optional available VESA bracket, ideal for space constrained environments.
- ▶ **Dualview support**
The DVI-I port offers the possibility to connect one digital and one analog monitor via the optional Y-Cable.
- ▶ **Excellent price performance**
Low price with strong multimedia performance.
- ▶ **No moving parts, e.g. cooling fans**
The absence of moving parts means the devices are almost noiseless and fail-safe with minimal heat generation.






UD2-LX MULTIMEDIA

Free evaluation:
www.igel.com/evaluation



COLORS

-  white
-  dark blue
-  black

PERIPHERAL INTERFACES



IGEL UD2-LX MULTIMEDIA SPECIFICATIONS



SYSTEM

Available Operating Systems	IGEL Linux
Management	IGEL Universal Management Suite included
Form Factor	Standard
Processor	Texas Instruments™ TMS320DM8148 Cortex A8, 1 GHz

MEMORY

RAM	1 GB DDR3
Flash Memory	2 GB

GRAPHICS

Video Memory	64 MB shared memory
Ports	1x DVI-I (DVI-to-VGA adapter included)
Supported Resolutions	1920 x 1200, Dualview

NETWORK

Ethernet	10/100/1000 Base-T
----------	--------------------

AUDIO

Chipset	TI DM8148 SoC
Ports	Front: 1x line-out, 1x mic-in
Speakers	1x internal

PERIPHERAL INTERFACES

Serial	Optional, via USB-to-Serial adapter
Parallel	Optional, via USB-to-Parallel adapter
USB 2.0	4x back

DIMENSIONS

Device (D x W x H), upright	203 x 55 x 208 mm
Packaging (D x W x H), horizontal	268 x 112 x 264 mm
Weight	1.2 kg

ENVIRONMENT

Cooling	Fanless convection
Operating Temperature	0° to 40° C (vertical) 0° to 35° C (horizontal, with rubber feet)
Operating Humidity	10% – 80%, non-condensing

POWER

Input	Auto sensing 100~240 VAC / 50~60 Hz
Power Supply	External
Power Consumption: Idle / Sleep Mode	7W / < 1W

OPTIONS

VESA mount	For mounting on the back of a monitor
Rubber feet	For horizontal placement of the device
Dualview Y-Cable	For DVI-I to DVI-D + VGA. Connect two monitors
USB-to-Serial adapter	For connecting peripherals that require a serial port
USB-to-Parallel adapter	For connecting printers that require a parallel port

After purchase, just register with us online, and all your IGEL thin clients UD2, UD3, and UD5 will be upgraded from a standard 2-year to a 5-year hardware warranty, according to our end customer hardware warranty declaration, at no additional cost. The UD9 series will be upgraded to a 3-year hardware warranty. The warranty upgrade does not cover any additional hardware options. IGEL is a registered trademark of IGEL Technology GmbH. All hardware and software names are registered trademarks of the respective manufacturers. Errors and omissions excepted. Subject to change without notice.

©10/2012 IGEL Technology | 85-EN-10-2 | WEEE-Reg.-Nr. DE 79295479

IGEL Technology GmbH | info@igel.com | www.igel.com

GERMANY
Augsburg · Bremen
info@igel.de
www.igel.de

UNITED KINGDOM
Reading
info@igel.com
www.igel.co.uk

FRANCE
Paris
france@igel.com
www.igel.fr

THE NETHERLANDS
Utrecht
benelux@igel.com
www.igel.nl

UNITED STATES
Cincinnati
info@igelamerica.com
www.igelamerica.com

CHINA
Hong Kong · Beijing · Shanghai
infochina@igel.com
www.igel.com/cn

SINGAPORE
info@igel.com
www.igel.sg

info@igel.com
www.igel.com



thin clients | development | services | solutions

Many functions. One device.