

IGEL UD9

THE POWERFUL ALL-IN-ONE ENDPOINT SOLUTION FOR THE HIGH-PERFORMANCE WORKER.

IGEL UD9 is a powerful integrated solution for the future workplace. This compact all-in-one platform allows access to all major central computing infrastructures and seamlessly supports an extensive range of tasks

- **Maximum Performance**
A quad core processor, HD graphics and SSD flash enable high performance for the most demanding tasks.
- **Compact and convenient**
21.5-inch LCD display with optional touchscreen.
- **Optimal connectivity**
Provided by an optional integrated WLAN module, DisplayPort, PS/2, serial port and six USB ports
- **Security is paramount**
Two factor authentication and quick login, even for roaming users at shared workplaces

PRIMARY USES

CAD/CAM

Multimedia

Unified Communications

Healthcare ERP system access



TECHNICAL SPECIFICATION UD9

| SYSTEM | |
|--|--|
| Operating System | IGEL OS 10. Optional Microsoft Windows 10 IoT (W10) |
| Management | IGEL Universal Management Suite |
| Processor | Intel Celeron J1900 1.99 – 2.42 GHz (Quad-Core) |
| Chipset | Intel Bay Trail SoC |
| MEMORY | |
| RAM (DDR3L) | 2 GB (LX), 4 GB (W10) |
| Flash Memory | 4 GB (LX), 32 GB (W10), larger SSD modules on request |
| GRAPHICS | |
| Chipset | Intel HD Graphics |
| Video Memory | 128 – 512MB Shared Memory |
| Ports (supported resolutions) | 1x DisplayPort 1.1a (2560 x 1600) Dualview: Intern (FullHD) 1920 x 1080 |
| NETWORK | |
| Ethernet | 10/100/1000 Base-T |
| WLAN | optional, 802.11 a/b/g/n |
| AUDIO | |
| Chipset | Realtek High Definition Audio (ALC269) |
| Ports | 1x Line-out |
| Speakers | 2x back |
| PERIPHERAL INTERFACES | |
| PS/2 | 1x |
| Serial | 1x |
| USB 2.0 | 4x |
| USB 3.0 | 2x |
| Security Lock | 1x back |
| DISPLAY | |
| Size | 21.5" |
| Aspect Ratio | 16:9 |
| Brightness | 250 cd/m ² |
| Contrast Ratio | 1000:1 |
| Viewing Angle | 178/170 |
| Response time | 1,5 ms |
| DIMENSIONS | |
| Device (D x W x H), upright | With stand: 252.51 x 515 x 515.33 mm. Without stand: 85.65 x 515 x 331.28 mm |
| Packaging (D x W x H), horizontal | 650 x 335 x 465 mm |
| Weight | 8.12 kg (UD9); 9.26 kg (UD9 Touch), incl. foot |
| ENVIRONMENT | |
| Cooling | Fanless convection |
| Operating Temperature | 0 °C to 40 °C |
| Operating Humidity | 30 % – 90 %, non-condensing |
| POWER | |
| Input | Auto sensing 100 – 240 VAC / 50/60 Hz |
| Power Supply | External |
| Power Consumption: Idle / Sleep | 26 W / 3W |
| OPTIONS | |
| Touchscreen Display | For public facing or space-constraint environments |
| USB-to-Serial Adapter | For connecting peripherals that require a serial port |
| USB-to-Parallel Adapter | For connecting printers that require a parallel port |
| DisplayPort-DVI-Adapter | For connecting a monitor that requires a DVI port |
| Integrated Smartcard Reader | For secure smartcard-based authentication |
| Integrated WLAN Module | For environments with no physical network infrastructure |
| CERTIFIKATES | |
| CE, TÜV-GS, EPEAT Silver rated, cULus, ICES-003, FCC Class B, RCM, VCCI, Energy Star, BSMI | For questions about product compliance or certification, please contact regulatory.compliance@igel.com . |
| FURTHER INFORMATION RESSOURCES | |
| Hardware Manual, Safety Instructions, Warranty | https://kb.igel.com |
| Download current firmware | http://igel.com |

Request a demo: igel.com/hardware

Revolutionary in its
Simplicity